

**AUSTRALIAN CAPITAL TERRITORY
ELECTRICITY AND WATER ACT 1988
DETERMINATION OF CHARGES
NO 50 OF 1990**

DETERMINATION:

The Australian Capital Territory Electricity and Water Authority (ACTEW) under Section 48 of the Electricity and Water Act 1988, makes the following determination fixing the charges that are payable to ACTEW for or in connection with sewer and stormwater main connections.

<u>SERVICE</u>	<u>CHARGE</u> Not less than :
1. <u>SEWER MAINS</u>	\$
1.1 100 mm diameter junction into 150 mm diameter main	270.00
1.2 100 mm diameter junction into 225 mm diameter main	430.00
1.3 100 mm diameter junction into 300 mm diameter main	585.00
1.4 Breaking into existing 150 mm, 225 mm or 300 mm diameter main at a new manhole	480.00
1.5 Connection to existing standard manhole without drop	
100 mm or 150 mm diameter	505.00
225 mm diameter	625.00
1.6 150 mm connection to existing standard manhole including external drop of up to 2 metres	1890.00
Rate for each additional metre of drop	130.00
1.7 225 mm connection to existing standard manhole including external drop of up to 2 metres	2050.00
Rate for each additional metre of drop	150.00

		\$
1.8	Provide 100 mm or 150 mm diameter collar out of existing standard sewer manhole for house connection without drop	400.00
1.9	Connecting main to end of existing main or collar out existing manhole	
	150 mm diameter	285.00
	225 mm diameter	375.00
1.10	100 mm diameter PVC temporary connection to standard sewer manhole including removal of PVC pipe from manhole at completion of project	360.00
1.11	Alterations to height of manhole. Raise or lower manhole up to 300 mm where the only alteration is to the neck of the manhole and the total length of neck and ring does not exceed 450 mm	185.00
1.12	Supply and fit oversize manhole ring requiring alteration to manhole cone	280.00
1.13	Supply and fit "Gatic" type cover to an existing manhole	380.00
2.	<u>STORMWATER MAINS</u>	
2.1	100 mm or 150 mm diameter branch in 300 mm or larger main	105.00
2.2	100 mm, 150 mm or 225 mm diameter junction in 225 mm diameter main	400.00
2.3	100 mm, 150 mm or 225 mm diameter collar in existing standard stormwater manhole or sump	275.00
		\$
	Convert kerb inlet sumps to mountable type:	
2.4	Model P and Q - single	760.00
2.5	Model P, Q and R - double	810.00