

**Determination:**

The Australian Capital Territory Electricity and Water Authority (ACTEW) under section 48 of the *Electricity and Water Act 1988*, makes the following determination fixing the minimum charges that are payable to ACTEW for or in connection with water main connections

Service	Charge
	Not less than:
<b>1. Connection to existing main</b>	
1.1 Tapping into cast iron or ductile iron main	\$
20 mm diameter	107.00
25 mm diameter	122.00
1.2 Tapping into asbestos cement main (20 and 25 mm)	\$
Diameter of main—	
100 mm	202.00
150 mm	209.00
225 mm	218.00
The above charges apply to one site visit only. If subsequent visits are necessary due to inadequate excavation, etc., an additional charge of \$30.00 per visit will apply.	
<b>2. Insertion of a tee connection into an existing main</b>	
2.1 With a flanged branch.	\$
100 mm diameter main	788.00
150 mm diameter main	895.00
225 mm diameter main	1 209.00
300 mm diameter main	1 486.00
Note Refer to Item 3 for charge for stop cocks and valves on branch connections.	
2.2 Additional charge:	
With a flanged socket:	\$
100 mm diameter main	43.00
150 mm diameter main	64.00
225 mm diameter main	149.00
300 mm diameter main	224.00
With a socketed branch:	\$
100 mm diameter main	836.00
150 mm diameter main	959.00
225 mm diameter main	1 422.00
300 mm diameter main	1 704.00
<b>3. Supply and installation of stop, valve or stop cock</b>	
3.1 Charge when installed at same time as tee connection (Item 2.1)	\$
40 mm Brass stop cock	138.00
50 mm Brass stop cock	160.00
65 mm Brass stop cock	218.00
80 mm Brass stop cock	245.00
100 mm Brass stop cock	538.00
100 mm Cast iron stop valve	288.00
150 mm Cast iron stop valve	442.00
225 mm Cast iron stop valve	1 241.00
300 mm Cast iron stop valve	1 363.00
3.2 Where installed on an existing flanged tee connection	
Charges in 3.1 above plus	266.00
3.3 Installation of stop valves in existing mains and service lines	

	\$
100 mm diameter cast iron stop valve	740.00
150 mm diameter cast iron stop valve	927.00
225 mm diameter cast iron stop valve	1 906.00
300 mm diameter cast iron stop valve	2 237.00

Note Valve covers, indicators, etc., are not included. However, these must be fixed by the contractor where any cast iron valve is installed.

**4. Removal of end cap and connection to main**

	\$
100 mm diameter	777.00
150 mm diameter	857.00
225 mm diameter	1076.00
300 mm diameter	1310.00

Note: Above charges include supply of gibault type joints only. These charges do not include the pipes which are to be supplied by the Contractor.

The charges include excavation behind and removal of anchor blocks.

Where end caps are greater than 5 m apart an additional charge may be made for excavation by ACTEW

**5. End capping of main**

5.1 Installation of single end cap

	\$
100 mm diameter	543.00
150 mm diameter	554.00
225 mm diameter	623.00
300 mm diameter	692.00

5.2 Installation of double end caps (back to back)

As above, plus the cost of an additional end cap at the charge shown below.

	\$
100 mm diameter	27.00
150 mm diameter	32.00
225 mm diameter	75.00
300 mm diameter	154.00

5.3 Installation of temporary double end caps, removal and reconnection

	\$
100 mm diameter	873.00
150 mm diameter	953.00
225 mm diameter	1118.00
300 mm diameter	1358.00

**6. Removal of cast iron socketed tee connection, cross connection or stop valve**

	\$
100 mm diameter	485.00
150 mm diameter	564.00
225 mm diameter	724.00
300 mm diameter	959.00

Note: The make-up piece of pipe is included in the applicable charge.

**7. Supply of socketed taper**

	\$
150 mm × 100 mm diameter	75.00
225 mm × 100 mm diameter	80.00
225 mm × 150 mm diameter	122.00
300 mm × 100 mm diameter	
300 mm × 150 mm diameter	
300 mm × 225 mm diameter	128.00

Note: These charges apply to tapers which are required as part of work associated with Items 2, 4, 5 and 9.

**8 Installation of fire hydrant**

8.1 Where insertion of hydrant tee is required	\$
100 mm diameter Tee	927 00
150 mm diameter Tee	1033 00
225 mm diameter Tee	1347 00
300 mm diameter Tee	1619 00

8.2 Installation on an existing tee connection 373 00

Note The charge for 8.1 and 8.2 applies only when fixing a hydrant to main laid at standard depth. Where the main exceeds this depth, additional risers can be supplied at the rates indicated below in 8.3

8.3 Additional hydrant riser	
100 mm to 375 mm long	32 00
450 mm to 600 mm long	69 00

Note Hydrant covers and indicators, etc., are to be supplied and fixed by the Contractor

**9 Insertion of socketed bend on existing main**

	\$
100 mm diameter	761 00
150 mm diameter	825 00
225 mm diameter	1 076.00
300 mm diameter	1 363.00

Note These charges do not apply where a bend is required to correct misalignment errors immediately adjacent to new connections. In this case, bends where approved, are to be supplied by the Contractor.

**10 Testing of main**

Minimum charge	\$
This includes four hours hire of equipment and operators	378 00
Hourly rate	
This will apply to all hours worked over and above the minimum time of four hours	85 00

Note In case of test failure, the minimum charge will apply to every subsequent test

**11 Supply and fix stop valve locking cover**

186.00

Note. This charge includes the installation and removal at a later date.

**12 Installation of metered overhead filling point**

12.1 By connection to existing hydrant tee	959.00
12.2 Where a new tee connection has to be inserted in the main	
Main diameter	

	\$
100 mm diameter	1 598 00
150 mm diameter	1 704 00
225 mm diameter	2 024 00
300 mm diameter	2 290 00

12.3 A reduction applies where the standpipe and support is supplied by the contractor 202 00

12.4 A reduction also applies to an un-metered standpipe 91 00

Note The above charges include a provision for removal on completion of project, and urgent and minor maintenance once erected. However, where major damage occurs the cost of repairs may be charged direct to the contractor for whom the installation was made.

**13. Disconnection of water service**

Note The following charges make allowance for excavation, backfilling and restoration of area

	\$
13.1 Service 20 mm to 32 mm diameter including (main cock connection)	272.00
13.2 Service 32 mm to 150 mm diameter including (flanged Tee connection)	373 00
13.3 Service 100 mm or 150 mm on mains of following sizes (involves removal of socketed tee connection and reinstating air)	
Main diameter	\$
100 mm diameter	825 00
150 mm diameter	884 00
225 mm diameter	1 203 00
300 mm diameter	1 400 00

Note This involves removal of Tee connection and main restoration