Determination

The Australian Capital Territory Electricity and Water Authority (ACTEW) under section 48 of the *Electricity* and Water Act 1988, makes the following determination fixing the charges that are payable to ACTEW for or in connection with sewer and stormwater main connections.

			Charge Not less
	Serv	than	
1	Sewe	\$	
	11	100 mm diameter junction into 150 mm diameter main	266 00
	1.2	100 mm diameter junction into 225 mm diameter main	389 00
	13	100 mm diameter junction into 300 mm diameter main	548 00
	1 4	Breaking into existing 150 mm, 225 mm or 300 mm diameter main at a new manhole	479.00
	1 5	Connection to existing standard man- hole without drop	
		100 mm or 150 mm diameter	479 00
		225 mm diameter	602 00
	1.6	150 mm connection to existing standard manhole including external drop of up	
		to 2 metres	1038.00
		Rate for each additional metre of drop	101.00
	17	225 mm connection to existing standard manhole including external drop of up to 2 metres	1251.00
		Rate for each additional metre of drop	112.00
	18	Provide 100 mm or 150 mm diameter collar out of existing standard sewer	112.00
		manhole for house connection without drop	399.00
	19	Connecting main to end of existing main or collar out existing manhole	
		150 mm diameter	266 00
		225 mm diameter	357 00
	1 10	100 mm diameter PVC temporary connection to standard sewer manhole including removal of PVC pipe from	357 00
	1 11	manhole at completion of project Alterations to height of manhole. Raise	351 00
	1.11	or lower manhole up to 300 mm where the only alteration is to the neck of the manhole and the total length of neck	
		and ring does not exceed 450 mm	176 00
	1.12	Supply and fit oversize manhole ring requiring alteration to manhole cone	325 00

Australian Capital Territory Gazette No ACT 11, 2 August 1989

	1.13	Supply and fit 'Gatic' type cover to an existing manhole	325.00
2.	Stor		
	21	100 mm or 150 mm diameter branch in 300 mm or larger main	101 00
	22	100 mm, 150 mm or 225 mm diameter junction in 225 mm diameter main	304 00
	2.3	100 mm, 150 mm or 225 mm diameter collar in existing standard stormwater manhole or sump	272 00
	Convert kerb inlet sumps to mountable type		
	24	Model P and Q - single	735.00
	25	Model P, Q and R - double	788.00