

**AUSTRALIAN CAPITAL TERRITORY
ELECTRICITY AND WATER ACT 1988
DETERMINATION OF CHARGES
NO. 5 OF 1991**

DETERMINATION:

The Australian Capital Territory Electricity and Water Authority (ACTEW) under Section 48 of the Electricity and Water Act 1988, makes the following determination: [In respect of services relating to Water Mains.]

<u>SERVICE</u>	<u>CHARGE</u>
1. <u>CONNECTION TO EXISTING MAIN</u>	
1.1 Tapping into Cast Iron or Ductile Iron Main	\$
20 mm diameter tapping	185.00
25 mm diameter tapping	200.00
1.2 Tapping into Main Where Tapping Band is Required (20 and 25 mm)	\$
100 mm diameter main	280.00
150 mm diameter main	285.00
225 mm diameter main	300.00

The above charges apply to one site visit only. If subsequent visits are necessary due to inadequate excavation, etc., an additional charge of \$30.00 per visit will apply.

2. INSERTION OF A TEE CONNECTION INTO AN EXISTING MAIN

2.1 With a Flanged Branch	\$
100 mm diameter main	1340.00
150 mm diameter main	1550.00
225 mm diameter main	2100.00
300 mm diameter main	2670.00

Note: Refer to Item 3 for charge for stop cocks and valves on branch connections.

2.2 Additional charge with a flanged socket:	\$
100 mm diameter	50.00
150 mm diameter	90.00
225 mm diameter	220.00
300 mm diameter	330.00

3. SUPPLY AND INSTALLATION OF STOP VALVE OR STOP COCK

3.1	Where installed at same time as tee connection (item 2.1)	\$
	40 mm brass stop cock	185.00
	50 mm brass stop cock	210.00
	65 mm brass stop cock	275.00
	80 mm brass stop cock	320.00
	100 mm cast iron stop valve	400.00
	150 mm cast iron stop valve	545.00
	225 mm cast iron stop valve	1365.00
	300 mm cast iron stop valve	1975.00

3.2 Where installed on an existing flanged tee connection:

Charges in 3.1 above plus \$400.00

3.3 Installation of stop valves in existing mains and service lines \$

	100 mm diameter cast iron stop valve	1350.00
	150 mm diameter cast iron stop valve	1480.00
	225 mm diameter cast iron stop valve	2650.00
	300 mm diameter cast iron stop valve	3280.00

Note: Valve covers, indicators, etc., are not included. However, these must be fixed by the Contractor where any cast iron valve is installed.

4. REMOVAL OF END CAP AND CONNECTION TO MAIN \$

	100 mm diameter	1150.00
	150 mm diameter	1280.00
	225 mm diameter	2050.00
	300 mm diameter	2295.00

Note: Above charges include supply of gibault type joints only. These charges do not include the pipes which are to be supplied by the Contractor.

Excavation behind and removal of anchor blocks prior to connection will be carried out by ACTEW.

Where end caps are greater than 5 m apart an additional charge may be made for excavation by ACTEW.

5. END CAPPING OF MAIN

\$

5.1 Installation of Single End Cap

100 mm diameter	810.00
150 mm diameter	825.00
225 mm diameter	950.00
300 mm diameter	1030.00

5.2 Installation of Double End Caps (back to back)

As above, plus the cost of an additional end cap at the charge shown below.

100 mm diameter	35.00
150 mm diameter	35.00
225 mm diameter	75.00
300 mm diameter	155.00

5.3 Installation of temporary double end caps, removal, recovery & reconnection

100 mm diameter	1305.00
150 mm diameter	1440.00
225 mm diameter	2115.00
300 mm diameter	2360.00

6. REMOVAL OF CAST IRON SOCKETED TEE CONNECTION, CROSS CONNECTION OR STOP VALVE

\$

100 mm diameter	730.00
150 mm diameter	850.00
225 mm diameter	1530.00
300 mm diameter	1770.00

Note: The make-up piece of pipe is included in the applicable charge.

7. SUPPLY AND INSTALLATION OF SOCKETED TAPER

\$

150 mm x 100 mm diameter	70.00
225 mm x 100 mm diameter	235.00
225 mm x 150 mm diameter	235.00
300 mm x 100 mm diameter	390.00
300 mm x 150 mm diameter	390.00
300 mm x 225 mm diameter	390.00

Note: These charges apply to tapers which are required as part of work associated with Items 2, 3, 5, 6 and 9.

GOVERNMENT NOTICES Continued

8. INSTALLATION OF FIRE HYDRANT \$

8.1	Where insertion of hydrant tee is required	
	100 mm diameter Tee	1310.00
	150 mm diameter Tee	1450.00
	225 mm diameter Tee	2250.00
	300 mm diameter Tee	2610.00
8.2	Installation on an existing tee connection	560.00

Note: The charge for 8.1 and 8.2 applies only when fixing a hydrant to main laid at standard depth. Where the main exceeds this depth, additional risers can be supplied at the rates indicated below in 8.3.

8.3	Additional hydrant riser	
	100 mm to 375 mm long	30.00
	450 mm to 600 mm long	90.00

Note: Hydrant covers and indicators, etc., are to be supplied and fixed by the Contractor.

9. INSERTION OF SOCKETED BEND ON EXISTING MAIN \$

	100 mm diameter	1135.00
	150 mm diameter	1230.00
	225 mm diameter	1895.00
	300 mm	2345.00

Note: These charges do not apply where a bend is required to correct misalignment errors immediately adjacent to new connections. In this case, bends where approved, are to be supplied by the Contractor.

10. TESTING OF MAIN \$Basic Charge

This includes 4 hours hire of equipment and operators. 570.00

Hourly Rate

This will apply to all hours worked over and above the minimum time of 4 hours
- Normal hours 120.00

Note: In case of test failure, the basic charge will apply to every subsequent test.

11. SUPPLY AND FIX STOP VALVE LOCKING COVER \$240.00

Note: This charge includes the installation and removal at a later date.

12. INSTALLATION OF METERED OVERHEAD FILLING POINT

12.1 By connection to existing hydrant tee \$1425.00

12.2 Where a new tee connection has to be inserted in the main

Main Diameter

100 mm 2215.00

150 mm 2430.00

225 mm 3275.00

300 mm 3630.00

12.3 A reduction applies where the standpipe and support is supplied by the Contractor \$260.00

12.4 A reduction also applies to an unmetered standpipe \$90.00

Note: The above charges include a provision for removal on completion of project, and urgent and minor maintenance once erected. However, where major damage occurs the cost of repairs may be charged direct to the Contractor for whom the installation was made.

13. DISCONNECTION OF WATER SERVICE \$

Note: The following charges make allowance for excavation, backfilling and restoration of area

13.1 Service 20 mm to 32 mm diameter (including main cock connection) 400.00

13.2 Service 32 mm to 150 mm diameter (including flanged Tee connection) 560.00

13.3 Service 100 mm or 150 mm on mains of following sizes

100 mm diameter main	1225.00
150 mm diameter main	1325.00
225 mm diameter main	1675.00
300 mm diameter main	1850.00

Note: This involves removal of Tee connection and main restoration.