

**AUSTRALIAN CAPITAL TERRITORY  
ELECTRICITY AND WATER ACT 1988  
DETERMINATION OF CHARGES  
NO. 6 OF 1991**

**DETERMINATION:**

The Australian Capital Territory Electricity and Water Authority (ACTEW) under Section 48 of the Electricity and Water Act 1988, makes the following determination fixing the charges that are payable to ACTEW for or in connection with sewer and stormwater main connections.

<u>SERVICE</u>	<u>CHARGE</u>
1. <b><u>SEWER MAINS</u></b>	<b>\$</b>
1.1 100 mm diameter junction into 150 mm diameter main	375.00
1.2 100 mm diameter junction into 225 mm diameter main	590.00
1.3 100 mm diameter junction into 300 mm diameter main	800.00
1.4 Breaking into existing 150 mm, 225 mm or 300 mm diameter main at a new manhole	540.00
1.5 Connection to existing standard manhole without drop	
100 mm or 150 mm diameter	655.00
225 mm diameter	755.00
1.6 150 mm connection to existing standard manhole including external drop of up to 2 metres	2830.00
Rate for each additional metre of drop	130.00
1.7 225 mm connection to existing standard manhole including external drop of up to 2 metres	2870.00

	Rate for each additional metre of drop	150.00
1.8	Provide 100 mm or 150 mm diameter collar out of existing standard sewer manhole for house connection without drop	495.00
1.9	Connecting main to end of existing main or collar out existing manhole 150 mm diameter	375.00
	225 mm diameter	450.00
1.10	100 mm diameter PVC temporary connection to standard sewer manhole including removal of PVC pipe from manhole at completion of project	380.00
1.11	Alterations to height of manhole. Raise or lower manhole up to 300 mm where the only alteration is to the neck of the manhole and the total length of neck and ring does not exceed 450 mm	235.00
1.12	Supply and fit oversize manhole ring requiring alteration to manhole cone	330.00
1.13	Supply and fit "Gatic" type cover to an existing manhole	410.00
2.	<b><u>STORMWATER MAINS</u></b>	
2.1	100 mm or 150 mm diameter branch in 300 mm or larger main	135.00
2.2	100 mm, 150 mm or 225 mm diameter junction in 225 mm diameter main	465.00
2.3	100 mm, 150 mm or 225 mm diameter collar in existing standard stormwater manhole or sump	380.00
	Convert kerb inlet sumps to mountable type:	
2.4	Model P and Q - single	910.00
2.5	Model P, Q and R - double	980.00