

**AUSTRALIAN CAPITAL TERRITORY
ELECTRICITY AND WATER ACT
DETERMINATION OF CHARGE
NO. 6 OF 1992**

DETERMINATION:

The Australian Capital Territory Electricity and Water Authority (ACTEW) under Section 48 of the Electricity and Water Act 1988, makes the following determination fixing the charges that are payable to ACTEW for or in connection with sewer and stormwater main connections. The charges determined hereunder come into effect on and from 1 July 1992.

<u>SERVICE</u>	<u>CHARGE</u>
1. SEWER MAINS	\$
1.1 100 mm diameter junction into 150 mm diameter main	400.00
1.2 100 mm diameter junction into 225 mm diameter main	630.00
1.3 100 mm diameter junction into 300 mm diameter main	860.00
1.4 Breaking into existing 150 mm, 225 mm or 300 mm diameter main at a new manhole	590.00
1.5 Connection to existing standard manhole without drop	
100 mm or 150 mm diameter	700.00
225 mm diameter	810.00
1.6 150 mm connection to existing standard manhole including external drop of up to 2 metres	2830.00
Rate for each additional metre of drop	130.00
1.7 225 mm connection to existing standard manhole including external drop of up to 2 metres	2870.00
Rate for each additional metre of drop	150.00
1.8 Provide 100 mm or 150 mm diameter collar out of existing standard sewer manhole for house connection without drop	540.00

	\$
1.9	Connecting main to end of existing main or collar out existing manhole
	150 mm diameter 375.00
	225 mm diameter 450.00
1.10	100 mm diameter PVC temporary connection to standard sewer manhole including removal of PVC pipe from manhole at completion of project 420.00
1.11	Alterations to height of manhole. Raise or lower manhole up to 300 mm where the only alteration is to the neck of the manhole and the total length of neck and ring does not exceed 450 mm 270.00
1.12	Supply and fit oversize manhole ring requiring alteration to manhole cone 390.00
1.13	Supply and fit "Gatic" type cover to an existing manhole 460.00
2.	STORMWATER MAINS
2.1	100 mm or 150 mm diameter branch in 300 mm or larger main 150.00
2.2	100 mm, 150 mm or 225 mm diameter junction in 225 mm diameter main 510.00
2.3	100 mm, 150 mm or 225 mm diameter collar in existing standard stormwater manhole or sump 380.00
	Convert kerb inlet sumps to mountable type:
2.4	Model P and Q - single 980.00
2.5	Model P, Q and R - double 1050.00