

ELECTRICITY AND WATER ACT 1988
DETERMINATION OF CHARGES
NO. 6 OF 1995

DETERMINATION:

The Australian Capital Territory Electricity and Water Authority (ACTEW) under Section 48 of the Electricity and Water Act 1988, makes the following determination in respect of services relating to Water Mains. The charges determined hereunder come into effect on and from 1 July 1995.

SERVICE	CHARGE \$
1. CONNECTION TO EXISTING MAIN	
1.1 Tapping into Cast Iron or Ductile Iron main	
20mm diameter tapping	205.00
25mm diameter tapping	220.00
1.2 Tapping into Main where Tapping Band is required (20 and 25mm)	
100mm diameter main	305.00
150mm diameter main	310.00
225mm diameter main	330.00

The above charges apply to one site visit only. If subsequent visits are necessary due to inadequate excavation etc, an additional charge of \$35.00 per visit will apply.

2. INSERTION OF A TEE CONNECTION INTO AN EXISTING MAIN

2.1 With a flanged branch	
100mm diameter main	1480.00
150mm diameter main	1690.00
225mm diameter main	2215.00
300mm diameter main	2815.00

Note: Refer to Item 3 for charge for stop cocks and valves on branch connections.

2.2 Additional charge with a flanged socket	
100mm diameter	50.00
150mm diameter	90.00
225mm diameter	230.00
300mm diameter	350.00

3. SUPPLY & INSTALLATION OF STOP VALVE OR STOP COCKS

3.1 Where installed at same time as tee connection (item 2.1)

40mm brass stop cock	195.00
50mm brass stop cock	220.00
65mm brass stopcock	290.00
80mm brass stop cock	340.00
100mm cast iron stop valve	420.00
150mm cast iron stop valve	575.00
225mm cast iron stop valve	1440.00
300mm cast iron stop valve	2085.00

3.2 Where installed on an existing flanged tee connection:

Charges in 3.1 above plus	443.00
---------------------------	--------

3.3 Installation of stop valves in existing mains and service lines

100mm diameter cast iron stop valve	1425.00
150mm diameter cast iron stop valve	1560.00
225mm diameter cast iron stop valve	3045.00
300mm diameter cast iron stop valve	3725.00

Note: Valve covers, indicators etc are not included. However these must be fixed by the Contractor where any cast iron valve is installed

4. REMOVAL OF END CAP AND CONNECTION TO MAIN

100mm diameter	1225.00
150mm diameter	1350.00
225mm diameter	2165.00
300mm diameter	2420.00

Note: Above charges include supply of gibault type joints only. These charges do not included the pipes which are to be supplied by the Contractor.

Excavation behind and removal of anchor blocks prior to connection will be carried out by ACTEW.

Where end caps are greater than 5m apart an additional charge may be made for excavation by ACTEW.

5 END CAPPING OF MAIN

5.1 Installation of Single End Cap

100mm diameter	895.00
150mm diameter	910.00
225mm diameter	1055.00
300mm diameter	1140.00

- 5.2 Installation of Double End Caps (back to back).
As above, plus the cost of an additional end cap at
the charge shown below.

100mm diameter	35.00
150mm diameter	35.00
225mm diameter	75.00
300mm diameter	165.00

- 5.3 Installation of temporary double end caps,
removal, recovery & reconnection

100mm diameter	1445.00
150mm diameter	1595.00
225mm diameter	2345.00
300mm diameter	2615.00

6. **REMOVAL OF CAST IRON SOCKETED TEE CONNECTION, CROSS
CONNECTION OR STOP VALVE**

100mm diameter	810.00
150mm diameter	940.00
225mm diameter	1690.00
300mm diameter	1960.00

Note: The make-up piece of pipe is included in the applicable charge.

7. **SUPPLY AND INSTALLATION OF SOCKETED TAPER**

150mm x 100mm diameter	70.00
225mm x 100mm diameter	245.00
225mm x 150mm diameter	245.00
300mm x 100mm diameter	410.00
300mm x 150mm diameter	410.00
300mm x 225mm diameter	410.00

Note These charges apply to tapers which are required as
part of work associated with Items 2, 3, 5, 6 and 9.

8. **INSTALLATION OF FIRE HYDRANT**

- 8.1 Where insertion of hydrant tee is required

100mm diameter tee	1385.00
150mm diameter tee	1530.00
225mm diameter tee	2375.00
300mm diameter tee	2780.00

- 8.2 Installation on an existing tee connection 625.00

Note The charge for 8.1 and 8.2 applies only when fixing a hydrant to main laid at
standard depth. Where the main exceeds this depth, additional risers can be
supplied at the rates indicated below in 8.3.

8.3 Additional hydrant riser

100mm to 375mm long	31.00
450mm to 600mm long	93.00

Note Hydrant covers and indicators etc, are to be supplied and fixed by the Contractor.

9.0 INSERTION OF SOCKETED BEND ON EXISTING MAIN

100mm diameter	1200.00
150mm diameter	1300.00
225mm diameter	2000.00
300mm diameter	2475.00

Note These charges do not apply where a bend is required to correct misalignment errors immediately adjacent to new connections. In this case, bends where approved, are to be supplied by the Contractor.

10.0 TESTING OF MAIN

Basic Charge	
This includes 4 hours hire of equipment & operators	635.00
 Hourly Rate	
This will apply to all hours worked over and above the minimum time of 4 hours	
- Normal hours	135.00

Note In case of test failure, the basic charge will apply to every subsequent test.

11.0 SUPPLY AND FIX STOP VALVE LOCKING COVER 265.00

Note This charge includes the installation and removal at a later date.

12. INSTALLATION OF METERED OVERHEAD FILLING POINT

12.1	By connection to existing hydrant tee	1505.00
12.2	Where a new tee connection has to be inserted in the main	
	Main Diameter	
	100mm	3185.00
	150mm	3410.00
	225mm	4300.00
	300mm	4675.00
12.3	A reduction applies where the standpipe and support is supplied by the Contractor.	275.00
12.4	A reduction also applies to an unmetered standpipe.	95.00

Note The above charges include a provision for removal on completion of project, and urgent and minor maintenance once erected. However, where major damage occurs the cost of repairs may be charged direct to the Contractor for whom the installation was made.

13.0 DISCONNECTION OF WATER SERVICE

Note The following charges make allowance for excavation, backfilling and restoration of area.

13.1	Service 20mm to 32mm diameter (including main cock connection)	450.00
13.2	Service 32mm to 150mm diameter (including flanged tee connection)	625.00
13.3	Service 100mm or 150mm on mains of following sizes	
	100mm diameter main	
	150mm diameter main	1310.00
	225mm diameter main	1400.00
	300mm diameter main	1765.00
		1980.00

Note This involves removal of tee connection and main restoration.

These service charges are minimum charges for work on basic installations, carried out in normal business hours unless otherwise stated. Charges for work of greater complexity, or outside these hours will be determined individually.