

## Regulations 1975 No. 14

### Regulations under the *Building and Services Ordinance 1924-1968*.\*

I, GORDON MUNRO BRYANT, the Minister of State for the Capital Territory, hereby make the following Regulations under the *Building and Services Ordinance 1924-1968*.

Dated this fourth day of August, 1975.

GORDON M. BRYANT  
Minister of State for the Capital Territory.

### AMENDMENTS OF THE CANBERRA SEWERAGE AND WATER SUPPLY REGULATIONS†

1. The Canberra Sewerage and Water Supply Regulations are amended as set out in the Schedule. Schedule of amendments.

2. Regulation 66 of the Canberra Sewerage and Water Supply Regulations is amended by omitting the table from sub-section (1) and substituting the following table:— Size and quality of pipes.

Sanitary Conveniences	Nominal bore	Wall thickness of lead pipe	Wall thickness of cast iron pipe
	millimetres	millimetres	millimetres
Lavatories and wash basins—			
single connexion .. .. .	32	2.50	..
where more than 1 connexion .. .. .	40	2.50	..
Bath, wash trough or wash tub, kitchen and			
pantry sink .. .. .	50	2.50	..
Stop sink .. .. .	65	3 <sup>a</sup>	6
Urinal .. .. .	40	3	6
Closet .. .. .	100	3	6 <sup>b</sup>

3. Regulation 93 of the Canberra Sewerage and Water Supply Regulations is amended by omitting sub-regulation (19) and substituting the following sub-regulation:— Provisions relating to meters.

- “(19) The sizes of stop tap ferrules shall be as follow:—
- For 50 millimetre and 75 millimetre meters .. 20 millimetres
  - For 100 millimetre meters .. .. . 25 millimetres
  - For meters larger than 100 millimetres .. .. . 40 millimetres.”

\* Notified in the *Australian Government Gazette* on 12 August 1975.  
† For references to the original Regulations and amendments made before 1960 see footnote on p. 93 of Vol. III of “Laws of the Australian Capital Territory 1911-1959” and, for later amendments, see Regulations 1962, No. 8.

Conditions to be observed in regard to tappings and services.

4. Regulation 96 of the Canberra Sewerage and Water Supply Regulations is amended—

(a) by omitting paragraph (e) and substituting the following paragraph:—

“(e) The maximum tapping that will be allowed without clip for each size of cast-iron main shall be as follows:—

For 75 millimetre and 100 millimetre pipes	.. ..	20 millimetre tapping
For 125 millimetre, 150 millimetre and 175 millimetre pipes	.. ..	25 millimetre tapping
For 200 millimetre pipes	.. ..	32 millimetre tapping
For 225 millimetre pipes	.. ..	40 millimetre tapping
For pipes larger than 225 millimetres	.. ..	50 millimetre tapping;”;

and

(b) by omitting the table in paragraph (q) and substituting the following table:—

“

Diameter of Trunk Service	Number of 25 millimetre branches only	Number of 20 millimetre branches only	Number of 15 millimetre branches only
20 millimetres	.. ..	..	2
25 millimetres	.. ..	2 or	5
32 millimetres	.. ..	2 or	10
40 millimetres	.. ..	3 or	15
50 millimetres	.. ..	6 or	30”.

Quality of fittings, &c.

5. Regulation 101 of the Canberra Sewerage and Water Supply Regulations is amended by omitting sub-regulation (3) and substituting the following sub-regulation:—

“(3) Lead piping shall be of the following masses:—

Diameter of pipe	Mass of pipe per metre	Diameter of pipe	Mass of pipe per metre
10 millimetres	.. 2.50 kilogrammes	25 millimetres	.. 7.20 kilogrammes
15 millimetres	.. 3 kilogrammes	32 millimetres	.. 11 kilogrammes
17 millimetres	.. 3.70 kilogrammes	40 millimetres	.. 15 kilogrammes
20 millimetres	.. 4.50 kilogrammes	50 millimetres	.. 22.50 kilogrammes”.

SCHEDULE

Regulation 1

Provisions amended	Omit—	Substitute—
Sub-regulation 4 (1)—“urinal stall”	.. .. 24 inches	600 millimetres
Regulation 9	.. .. s d 10 6	\$ c 1.00
Regulation 20	.. .. 2 6 s d 5 0 5 0 2 6 2 6	0.25 50 cents 50 cents 25 cents 25 cents
Regulation 21	.. .. Two shillings and sixpence	25 cents

SCHEDULE—continued

Provisions amended	Omit—	Substitute—
Regulation 30 .. ..	4 inches	100 millimetres
Sub-regulation 34 (2) ..	6 inches	150 millimetres
	4 feet	1.20 metres
Sub-regulation 34 (3) ..	$\frac{1}{8}$ -inch	6 millimetres
Sub-regulation 34 (4) ..	3 inches	75 millimetres
Sub-regulation 35 (1) ..	4-in.	100 millimetre
	1 foot in 40 feet	2.50 per cent.
	6-in.	150 millimetre
	1 foot in 60 feet	1.50 per cent.
	9-in.	225 millimetre
	1 foot in 300 feet	0.35 per cent.
	12-in.	300 millimetre
	1 foot in 400 feet	0.25 per cent.
Sub-regulation 35 (2) ..	4,6,9, or 12-in.	100, 150, 225 or 300 milli- metre
	1 in 10, 1 in 15, 1 in 20, or 1 in 25	10 per cent., 6.50 per cent., 5 per cent. or 4 per cent.
Regulation 38 .. ..	2 feet	500 millimetres
Sub-regulation 40 (3) ..	height of 1 foot	height of 300 millimetres
	layers of 1 foot	layers of 300 millimetres
Regulation 48 .. ..	30 feet	10 metres
Sub-regulation 52 (3) ..	2 feet	500 millimetres
Sub-regulation 54 (2) ..	6 inches	150 millimetres
	$6\frac{1}{2}$ inches	175 millimetres
Sub-regulation 54 (6) ..	$2\frac{1}{2}$ inches	60 millimetres
Regulation 55 .. ..	2 feet	600 millimetres
Sub-regulation 56 (2) ..	18 feet	5 metres
	6 feet	1.50 metres
	30 feet	9 metres
Sub-regulation 57 (1) ..	15 feet	6 metres
Sub-regulation 58 (2) ..	of not less than No. 20 stand- ard wire gauge	not less than 0.90 millimetre in diameter
Sub-regulation 59 (1) ..	12 feet	3.50 metres
	$\frac{1}{2}$ -in. galvanised wrought-iron pipe	wrought-iron pipe 15 milli- metres in diameter
Sub-regulation 59 (3) ..	15 feet above	4.50 metres above
	more than 15 feet	more than 4.50 metres
Sub-regulation 59 (4) ..	6 feet	2 metres
Sub-regulation 60 (2) ..	more than 6 feet	more than 2 metres
	height of 18 feet	height of 5 metres
	6 feet and under	2 metres and under
	2 feet	600 millimetres
	18 feet above	5 metres above
	at a height 6 feet	at a height 2 metres
Sub-paragraph 62 (2) (b) (i)	one hundred and ten degrees Fahrenheit	44 degrees Celsius
Sub-regulation 63 (4) ..	9 inches	200 millimetres
Sub-regulation 64 (6) ..	$1\frac{1}{2}$ inches in diameter	40 millimetres nominal bore
Sub-regulation 66 (4) ..	heavier than 6-lb. lead	thicker than 2.50 millimetre lead
Sub-regulation 66 (5) ..	three-sixteenths of an inch	4.75 millimetres
Sub-regulation 67 (3) ..	2 inches	50 millimetres
Regulation 69 .. ..	4 inch	100 millimetres
	3 inch	75 millimetres
	$2\frac{1}{2}$ inch	65 millimetres
	2 inch	50 millimetres
	$1\frac{1}{2}$ inch	40 millimetres
	$1\frac{1}{4}$ inch	32 millimetres
Sub-regulation 71 (2) ..	No. 22 standard gauge	0.70 millimetre thick
Sub-regulation 73 (1) ..	12 feet	4 metres
	18 feet	6 metres
Sub-regulation 73 (2) ..	12 feet	4 metres
Regulation 74 .. ..	2 ft. 6 in.	750 millimetre
Paragraph 77 (k) .. ..	weighing not less than 6 lb. per superficial foot	not less than 2.50 millimetres thick

## SCHEDULE—continued

Provisions amended	Omit—	Substitute—
Paragraph 77 (1) ..	nearer than 3 inches	nearer than 75 millimetres
	18 inches	500 millimetres
	3 inches in diameter	75 millimetres in diameter
Sub-regulation 78 (3) ..	2 feet	600 millimetres
Sub-regulation 78 (5) ..	2½ inches	60 millimetres
Sub-regulation 80 (10) ..	100 square feet	10 square metres
Sub-regulation 80 (13) ..	14 square feet	1.10 square metres
Sub-regulation 80 (14) ..	two square feet	0.20 square metre
Sub-regulation 80 (16) ..	9" x 6"	230 millimetres x 150 millimetres
	6"	150 millimetres
Sub-regulation 80 (17) ..	27 square inches	0.016 square metre
	six inches	150 millimetres
Sub-regulation 80 (19) ..	6 ft. 6 in.	2 metres
	2 ft. 9 in.	810 millimetres
	14 superficial feet	1.10 square metres
	2 inches	50 millimetres
	6 inches	150 millimetres
Sub-regulation 80 (20) ..	½ inch to the foot	4 per cent.
Sub-regulation 80 (21) ..	2½ inches	60 millimetres
Sub-regulation 80 (23) ..	not less than 6 lb. sheet lead	sheet lead not less than 2.50 millimetres thick
	3 inches	75 millimetres
	15 inches	400 millimetres
Sub-regulation 80 (24) ..	10½ inches by 9 inches	260 millimetres by 225 millimetres
Sub-regulation 80 (27) ..	two and one-half gallons capacity	11 litres capacity
	not less than two and one-half gallons and not more than two and one-half gallons	not less than 9 litres and not more than 11 litres
	two gallons	9 litres
Sub-regulation 80 (28) ..	5 ft. 9 in.	1.75 metres
	9 inches	225 millimetres
	5-in.	125 millimetre
Paragraph 80 (29) (a) ..	12 inches deep by 18 inches wide	300 millimetres deep by 450 millimetres wide
	1½ inches	32 millimetres
	¾-in. by 6-in. bolts	bolts 10 millimetres in diameter by 150 millimetres
Sub-regulation 80 (30) ..	50 gallons	200 litres
	16 gauge	1.60 millimetres thick
Sub-regulation 80 (31) ..	22 gauge iron or 5 lb. sheet lead	iron 0.70 millimetre thick or sheet lead 2.20 millimetres thick
	3 inches and provided with 1½-in. galvanized	75 millimetres and provided with 40 millimetre galvanized
	12 inches	300 millimetres
	a 1½-in. galvanized wrought-iron	a 40 millimetre galvanized wrought-iron
Paragraph 80 (32) (a) ..	not less than two nor more than three gallons	not less than 9 nor more than 14 litres
Sub-regulation 80 (33) ..	2 square feet	0.20 square metre
Sub-regulation 80 (35) ..	3 feet	1 metre
	of not less than No. 20 standard steel-wire gauge	not less than 0.90 millimetre thick
	2 inches to 4 inches	50 millimetres to 100 millimetres
Sub-regulation 80 (36) ..	three-sixteenths of an inch	5 millimetres
	2-inch	50 millimetre
	18 inches	500 millimetres
Sub-regulation 81 (1) ..	3 feet	1 metre
	12 superficial feet	1.20 square metres
Sub-regulation 81 (4) ..	4 ft. 6 in.	1.40 metres

SCHEDULE—continued

Provisions amended	Omit—	Substitute—
Paragraph 81 (5) (a)	9 inches	230 millimetres
	one-half inch	15 millimetre
Paragraph 81 (5) (b)	6 inches	150 millimetres
	one-half inch	15 millimetres
Sub-regulation 81 (9)	$\frac{3}{4}$ -in.	10 millimetre
Sub-regulation 81 (10)	6 ft. 6 in.	2 metres
Paragraph 81 (12) (a)	for 1-gallon cisterns— $\frac{1}{4}$ inch diameter	for 5 litre cisterns—20 millimetre diameter
Paragraph 81 (12) (b)	for 2-gallon cisterns—1 inch diameter	for 9 litre cisterns—25 millimetre diameter
Paragraph 81 (12) (c)	for 3-gallon cisterns— $1\frac{1}{4}$ inch diameter	for 14 litre cisterns—32 millimetre diameter
Sub-regulation 81 (16)	1 gallon for each 2 feet	4 litres for each 500 millimetres
Sub-regulation 81 (17)	$\frac{1}{2}$ inch to 1 foot	4 per cent.
Sub-regulation 82 (5)	18 inches	500 millimetres
Sub-regulation 84 (1)	not less than 5 lb. lead	lead not less than 2.20 millimetres thick
Sub-regulation 84 (2)	not less than 5 lb. lead	lead not less than 2.20 millimetres thick
	4 inches	100 millimetres
Sub-regulation 84 (5)	not less than 6 lb. per square foot	not less than 2.50 millimetres thick
	$1\frac{1}{2}$ lb. per square foot	0.80 millimetre thick
Sub-regulation 85 (3)	21 inches	0.50 metre
Sub-regulation 86 (4)	at least 5-16th inch by 6 inch bolts	bolts not less than 8 millimetres in diameter and 150 millimetres in length
Sub-regulation 87 (2)	6 inches	150 millimetres
Sub-regulation 88 (1)	2 inches	50 millimetres
Sub-regulation 88 (5)	2 inches	50 millimetres
Sub-regulation 91 (2)	Penalty: Ten pounds	Penalty: \$20
Sub-regulation 93 (3)	1,000,000 gallons	5,000 kilolitres
Sub-regulation 93 (4)	$\frac{1}{2}$ -in., $\frac{3}{4}$ -in., or 1-in.	15 millimetre, 20 millimetre, or 25 millimetre
	10, 15, or 30 gallons	50, 70 or 140 litres
Sub-regulation 93 (5)	3 feet	1 metre
Sub-regulation 93 (17)	2-in.	50 millimetre
Paragraph 96 (c)	$\frac{1}{2}$ inch	20 millimetres
Paragraph 96 (d)	$\frac{1}{2}$ inch	20 millimetres
Paragraph 96 (f)	2-in.	50 millimetre
	5-in.	125 millimetre
	3-in.	75 millimetre
	6-in.	150 millimetre
Paragraph 96 (j)	9 inches	225 millimetre
Paragraph 96 (r)	15 inches	350 millimetres
Regulation 97	2 inches	50 millimetres
Sub-regulation 100 (1)	Penalty: Five pounds, and, in addition, a penalty not exceeding Two pounds	Penalty: \$10 and, in addition, a penalty not exceeding \$4
Regulation 102	100 gallons	500 litres
Regulation 104	Penalty: Five pounds and, in addition, a penalty not exceeding Two pounds per day	Penalty: \$10 and, in addition, a penalty not exceeding \$4 per day
Regulation 105	3 inches wide by 2 inches thick	80 millimetres wide by 50 millimetres thick
Sub-regulation 106 (1)	Penalty: Five pounds	Penalty: \$10
Sub-regulation 106 (2)	Penalty: Five pounds	Penalty: \$10
Regulation 107	Penalty: Five pounds	Penalty: \$10
Regulation 108	Penalty: Five pounds, and, in the case of a continuing offence a further penalty not exceeding Two pounds	Penalty: \$10 and, in the case of a continuing offence, a further penalty not exceeding \$4
Sub-regulation 109 (2)	22 gauge galvanised sheet iron	galvanised sheet iron 0.70 millimetre thick
	$1\frac{1}{2}$ inches	40 millimetres

## SCHEDULE—continued

Provisions amended	Omit—	Substitute—
Sub-regulation 109 (3) ..	30 gallons 10 gallons 5 gallons 3 gallons	140 litres 50 litres 25 litres 14 litres
Sub-regulation 109 (7) ..	16 gauge	1.60 millimetres thick
Regulation 111 ..	Penalty: Five pounds	Penalty: \$10
Sub-regulation 112 (1) ..	Penalty: Five pounds	Penalty: \$10
Sub-regulation 112 (2) ..	Penalty: Five pounds	Penalty: \$10
Sub-regulation 114 (2) ..	Penalty: Five pounds	Penalty: \$10
Regulation 114B ..	Five pounds Ten pounds Ten shillings	\$10 \$20 \$1
The Schedule—		
Form A (fifth paragraph) ..	Ten shillings and six pence (10s. 6d.)	\$1
Form C (NOTE—paragraph 1)	2s. 6d.	25 cents
Form D (fifth paragraph) ..	Ten shillings and six pence	\$1
Form E (NOTE—paragraph 1)	2s. 6d.	25 cents
Form F (fifth paragraph) ..	Ten shillings and six pence (10s. 6d.)	\$1
Form G (NOTE—paragraph 1)	2s. 6d.	25 cents
Form H (fifth paragraph) ..	Ten shillings and six pence (10s. 6d.)	\$1
Form I (NOTE—paragraph 1)	2s. 6d.	25 cents